Water Quality Monitoring and Parameter Load Estimations in Lake Conway Point Remove Watershed, L'Anguille River Watershed, and Bayou Bartholomew

> Presented by: Dan DeVun, Equilibrium <u>devun@equilibrium-ar.org</u> <u>www.equilibrium-ar.org</u> 09/19/2014



Acknowledgements and Special Thanks

- EPA Region 6
- ANRC; Tony Ramick and Robbie Alberson
- Wesley Griffin
- Ouachita Baptist University
- Dr. Tim Knight
- Clark Kyper
- Dr. Joe Nix
- Natural State Streams
- Ecological Design Group
- Entergy, Inc.
- HDR, Inc.



Projects Primary Goal

By collecting, analyzing and reporting water quality and discharge data; provide monthly and annual parameter loadings, as well as unit area loadings in numerous 12 digit HUCs.



- Monitoring Structure Similar activities are implemented in each monitored watershed that support each project's primary goal.
- Water Quality Requirements Incorporates project design, collection methodology and analytical methodology to generate representative data and allow for an evaluation of water chemistry within the selected watersheds.
- **Discharge Requirements** Estimate the volume of water that passes the monitoring station during the sampling period.
- Data Compilation and Statistical Analysis Compile and statistically analyze the collected data to provide monthly, annual, and unit area loadings, as well as, compare results between monitoring stations.
- Reporting Requirements Provide the project participants with the project outcomes and make the results readily available to the natural resource and watershed professionals and the general public.



<u>Equilibrium's Water Quality</u> <u>Monitoring Requirements</u>

- Sample Types Discrete grab samples, when possible we collect depth integrated samples at the mid point of the stream
- Collection Frequency Once per week
- In-situ Parameters Temperature, dissolved oxygen, specific conductance, pH, and stage.
- Record Field Notes documentation that includes type of sample, time and date, site location, name of sampler, climatic characteristics during site visit, recognized problems, and corrective actions required or taken.



Equilibrium's Water Quality Monitoring Requirements (Continued)

- Laboratory Parameters TSS, Turbidity, Total Phosphorus, Total Kjeldahl Nitrogen, Nitrate-Nitrogen, Ammonia-Nitrogen, Total Nitrogen, Chloride and Sulfate.
- QAQC Samples Samples taken to insure representativeness of collected data. (include replicate, field blanks, split and spiked samples)



<u>Equilibrium's Discharge</u> <u>Requirements</u>

- Monitoring Station Location When possible, locate monitoring stations where existing USGS stations are located. Unfortunately only 2 of 25 stations are located at USGS stations...
- Discharge Parameters Stage, Profile, and Velocity
 - Stage Utilize pressure transducers to measure stage every 30 minutes. Additionally, manually measure stage at the time of water quality collection.
 - Profile survey and record the stream's cross sectional profile
 - Velocity utilize numerous instruments (electromagnetic and acoustic doppler methodologies) to calculate stream velocities



Equilibrium's Discharge Requirements (Continued)

 Discharge Measurements — Stream discharge is measured at numerous points throughout the hydrograph. We attempt to measure discharge at a minimal of three different stages of each categorical flow.

Low Flow, Mid Flow, High Flow

- Develop the Stage Rating Discharge Curve determine the mathematical relationship between stage and discharge for the measured discharge points.
- Utilize the Stage Rating Discharge Curve estimate daily discharge from the continuously collected stage data.



Data Compilation and Statistica 14.8 4593 7 05 14.8 35040 7.12 Analysis 7.05 14.8 45

- Compilation of collected data Laboratory Water Quality Data
 - In-situ Water Quality Data
 - Historical Water Quality Data
 - > QAQC Water Quality Data
 - Stage Data
 - Discharge Data
 - Historical Discharge Data
 - Precipitation Data
- Statistical Analysis
 - Statistical relationship between stage and discharge
 - Calculation of parameter loadings
 - > Statistical comparison between monitoring stations.



0.50

7.08

7.07

7.04

7.01

6.97

6.94

6.9

44.9

44.9

44.9

44.9

44.9

4/14/2014 9:10

1899

1900

1901

4/14/2014 9:10

7.04

7.04

7.03

7.02

7.02

7.01

7.01

14.8

14.8

14.8

14.8

14.8

14.8

9.6

22.8

1CC LCC

1CC

1CC

100

LCC

LCC

LCC

100

1CC

LCC

433

26

4.5

4.7 4.8

4.3 4.7

Reporting

- Provide all project participants with a final report.
- Provide public access of our data through WQX.
- Our collected data and analysis can be beneficial to numerous persons working in fields related to water quality and water quantity.





Lake Conway Point Remove Watershed Ten monitoring stations

Project Period is July 2011 – October 2014

Monitoring the "outfalls" of 12 digit HUC

Completing data collection phase, preparing Final Report

LCPR scored 91 in the Final Risk Assessment Matrix Percentile of the Arkansas' Nonpoint Source Pollution Watershed Risk Matrix and has been selected as a priority watershed.

NRCS identified LCPR as a priority in the Mississippi River Basin Healthy Watershed Initiative.

















Lake Conway Point Remove Watershed

Mean Parameter Concentrations (MG/I)										
	WF1	WF2	WF3	WF4	EF1	EF2	PR	СҮР	LCC	ос
ТР	0.069	0.039	0.049	0.121	0.047	0.09	0.103	0.131	0.067	0.151
TKN	1.138	0.424	0.398	0.661	0.399	0.682	0.677	0.741	0.472	1.066
Ammonia	0.245	0.038	0.031	0.038	0.023	0.114	0.063	0.061	0.032	0.102
Turbidity (NTU)	13.689	17.269	9.397	22.173	11.942	16.034	24.415	24.018	10.148	70.406
TSS	8.522	7.124	7.036	18.64	7.832	13.022	17.883	14.65	7.664	42.548
NO ₃ -N	1.065	0.65	0.924	1.055	1.163	1.141	1.192	1.227	1.221	2.728
Chloride	3.834	2.048	3.935	16.27	4.027	5.324	9.707	6.159	5.172	8.265
Sulfate	6.176	3.525	2.586	7.879	4.324	3.099	6.119	4.712	2.978	13.051



L'Anguille River Watershed Five monitoring stations

Current Project Period July 2012 – September 2015

Monitoring the "outfalls" of 12 digit HUC

Currently in data collection phase

- The L'Anguille River was included on the Arkansas 1998 303(d) list for not supporting aquat life due to siltation/turbidity and has been on each subsequent 303(d) list.
- ANRC has designated the watershed as a priority watershed.
- NRCS also identified the L'Anguille River as a priority in the Mississippi River Basin Healthy Watershed Initiative.



Priority Subwatersheds- Percentile Basis



Area: approx.12.% Sediment contribution: approx. 34%





Priority Ranking by SWAT Model

12-Digit HUC Name	Drainage Size (Acres)	Sediment Load (Percentile)	Total Phosphorus Load (Percentile)	Erosion Rate	Cartographic Score	
Copper Creek	12,056	80-100	60-80	Critical	Critical	
Prairie Creek	11,626	0-20	0-20	Critical	Critical	
Indian Creek	21,034	20-40	20-40	Moderate	Critical	
Upper Brushy Creek	21,718	40-60	0-20	Slight	Slight	
Middle Brushy Creek	31,947	0-20	40-60	Slight	Slight	
					Saraswat, et.al	







Hydrograph L'Anguille (Stage)



L'Anguille Watershed

Mean Parameter Concentrations (MG/I)									
	UB	MB	СС	PC	IC				
Acres	21,718	31,947	12,056	11,626	21,034				
ТР	0.44	0.43	0.45	0.36	0.41				
TKN	1.58	1.52	1.54	0.99	1.35				
Ammonia	0.16	0.09	0.26	0.05	0.11				
Turbidity (NTU)	113.03	138.45	58.15	108.61	82.43				
TSS	74.60	89.16	42.24	87.03	52.56				
NO ₃ -N	1.45	1.81	2.95	2.91	1.85				
Chloride	20.71	19.97	10.99	11.44	14.72				
Sulfate	10.58	11.58	12.48	13.54	17.85				



Bayou Bartholomew Watershed

Ten monitoring stations

Current Project Period July 2013 – September 2017

Focusing on the Deep Bayou and Cousart Bayou Subwatersheds

Currently in data collection phase

• The Bayou Bartholomew was included on the Arkansas 2012 303(d) for not supporting designated uses.

- ANRC has designated the watershed as a priority watershed.
- NRCS also identified the L'Anguille River as a priority in the Mississippi River Basin Healthy Watershed Initiative.





Arkansas 2006-2010 NPS Management Program Update Effective Date: October 1, 2005

Effective Date: October 1, 2005



Hydrograph Bayou Bartholomew (Stage)



Bayou Bartholomew Watershed

Mean Parameter Concentrations (MG/I)										
	B1	B2	B3	C1	C2	D1	D2	D3	D4	D5
ТР	0.26	0.34	0.37	0.80	0.47	0.45	0.45	0.43	0.42	0.49
TKN	0.94	1.17	1.12	1.89	1.41	1.41	1.34	1.34	1.29	1.39
Ammonia	0.05	0.08	0.07	0.42	0.13	0.11	0.18	0.11	0.13	0.12
Turbidity (NTU)	52.16	87.48	103.59	96.31	116.03	19.59	69.50	106.34	115.05	155.01
TSS	26.29	48.06	45.54	54.56	60.51	9.67	38.00	57.74	53.40	79.26
NO ₃ -N	4.21	4.11	4.11	2.89	7.23	0.94	1.28	8.73	5.59	5.00
Chloride	5.33	8.03	8.40	4.98	24.46	2.57	5.32	18.95	18.35	17.71
Sulfate	2.49	3.10	3.22	4.20	6.66	1.92	1.54	4.73	4.04	4.00















Project Difficulties

- Harsh Winter
- In Stream Activities
- Unnatural Discharges
- Equipment loss
- Discharge Measurements at 12 digit level





¿ Questions?

Thank You



www.equilibrium-ar.org